

In the Claims

1. (Currently amended) A wireless terminal comprising:

an antenna;

a first visual indicator that ~~begins providing~~ provides a visual indication to a user of said wireless terminal when a radio ~~begins~~ is transmitting and stops providing said visual indication when said radio is receiving; and

a signal lead for carrying an RF signal from said radio to said antenna and from said antenna to said radio and for carrying a first baseband signal from said radio to said first visual indicator for activating said first visual indicator.
2. (Original) The wireless terminal of claim 1 further comprising said radio.
3. (Original) The wireless terminal of claim 2 wherein said radio is integral to a PC radio card.
4. (Original) The wireless terminal of claim 1 wherein said signal lead is connected to said radio by a detachable connector.
5. (Original) The wireless terminal of claim 1 further comprising a second visual indicator that indicates when said radio is receiving and wherein said signal lead also carries a second baseband signal from said radio to said second visual indicator.

6. (Currently amended) A wireless terminal comprising:
- an antenna;
- a first visual indicator that ~~begins providing~~ provides a visual indication to a user of said wireless terminal when a radio ~~begins~~ is receiving and stops providing said visual indication when said radio is transmitting; and
- a signal lead for carrying an RF signal from said radio to said antenna and from said antenna to said radio and for carrying a first baseband signal from said radio to said first visual indicator for activating said first visual indicator.
7. (Original) The wireless terminal of claim 6 further comprising said radio.
8. (Original) The wireless terminal of claim 7 wherein said radio is integral to a PC radio card.
9. (Original) The wireless terminal of claim 6 wherein said signal lead is connected to said radio by a detachable connector.
10. (Original) The wireless terminal of claim 6 further comprising a second visual indicator that indicates when said radio is transmitting and wherein said signal lead also carries a second baseband signal from said radio to said second visual indicator.

11. (Currently amended) A wireless terminal comprising:

- a radio;
- an antenna;
- a first visual indicator that indicates to a user of said wireless terminal when said radio is operating; and
- a cable that is detachably connected to said radio and that is also connected to said antenna for carrying an RF signal and for carrying a baseband signal from said radio to said first visual indicator;

wherein said first visual indicator indicates when said radio ~~begins~~ is receiving and further comprising a second visual indicator that indicates when said radio ~~begins~~ is transmitting and wherein said cable also carries a second baseband signal from said radio to said second visual indicator.